



MHA ZENTGRAF Ball valve Series: BKHP500 Steel Cutting ring, heavy (S) PN500

Characteristics

Series: BKHP500

Norm: EN (DIN)

Construction type: 2-way

Housing construction: 3-part

Housing material: Steel

Material quality: Forged steel

Surface protection: Zinc Plated

Connection: Cutting ring, heavy (S)

Characteristics (2)

Standard connection: DIN 2353 / ISO 8434-1

Spindle material: Steel

Minimum medium temperature (continuous): -20 °C

Maximum medium temperature (continuous): 100 °C

Weight [kg]: 3.16 kg

Nominal inner diameter	External tube diameter of connection mm	Connection, gland nut mm	Pressure rating	Face to Face norm	Manual operation	Material ball	Seat material	Secondary spindle seal material	Body seal	Article
DN25	30	M 42x2	PN500	Manufacturer standard	Handle	Steel	POM	FPM (FKM)	FPM (FKM)	14612968
DN25	30	M 42x2	PN500	Manufacturer standard	Handle	Steel	POM	NBR	NBR	14288463

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.