

MHA ZENTGRAF Ball valve Series: BKHP500 Steel Internal thread (BSPP) PN500

Characteristics

Series: BKHP500 Norm: EN (DIN)

Construction type: 2-way Housing construction: 3-part Housing material: Steel Material quality: Forged steel Surface protection: Zinc Plated

Characteristics (2)

Connection: Internal thread (BSPP)

Minimum medium temperature (continuous): -20 °C Maximum medium temperature (continuous): 100 °C

Weight [kg]: 3.16 kg

Nominal inner diameter	Standard thread connection	Pressure rating	Face to Face norm	Manual operation	Material ball	Seat material	Spindle material	Secondary spindle seal material	Body seal	Article
1" (25)	ISO 228-1	PN500	Manufacturer standard	Handle	Steel	POM	Steel	FPM (FKM)	FPM (FKM)	14612969
1" (25)	ISO 228-1	PN500	Manufacturer standard	Handle	Steel	POM	Steel	NBR	NBR	14288284

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

PR1000488936219930_EN_28.09.2024