



MHA ZENTGRAF 3-Way ball valve Series: BK3 Steel Cutting ring, light (L) PN315/500

Characteristics

Series: BK3
Norm: EN (DIN)
Construction type: 3-way
Housing construction: 4-part
Housing material: Steel
Material quality: Forged steel
Surface protection: Zinc Plated
Connection: Cutting ring, light (L)
Standard connection: DIN 2353 / ISO 8434-1

Characteristics (2)

Material ball: Steel
Seat material: POM
Spindle material: Steel
Minimum medium temperature (continuous): -20 °C
Maximum medium temperature (continuous): 100 °C

Nominal inner diameter	External tube diameter of connection	Connection, gland nut	Pressure rating	Face to Face norm	Manual operation	Ball bore	Secondary spindle seal material	Body seal	Weight	Article
	mm	mm							kg	
DN04	6	M 12x1.5	PN500	Manufacturer standard	Handle	L-bore	FPM (FKM)	FPM (FKM)	0.4	14613095
DN04	6	M 12x1.5	PN500	Manufacturer standard	Handle	T-bore	NBR	NBR	0.4	14288604
DN04	6	M 12x1.5	PN500	Manufacturer standard	Handle	L-bore	NBR	NBR	0.4	14288602
DN06	8	M 14x1.5	PN500	Manufacturer standard	Handle	L-bore	FPM (FKM)	FPM (FKM)	0.46	14613100
DN06	8	M 14x1.5	PN500	Manufacturer standard	Handle	T-bore	NBR	NBR	0.46	14288609
DN06	8	M 14x1.5	PN500	Manufacturer standard	Handle	L-bore	NBR	NBR	0.46	14288607
DN08	10	M 16x1.5	PN500	Manufacturer standard	Handle	L-bore	FPM (FKM)	FPM (FKM)	0.46	14613103
DN08	10	M 16x1.5	PN500	Manufacturer standard	Handle	T-bore	FPM (FKM)	FPM (FKM)	0.46	14613104
DN08	10	M 16x1.5	PN500	Manufacturer standard	Handle	T-bore	NBR	NBR	0.46	14288526
DN08	10	M 16x1.5	PN500	Manufacturer standard	Handle	L-bore	NBR	NBR	0.46	14288524
DN10	12	M 18x1.5	PN500	Manufacturer standard	Handle	L-bore	FPM (FKM)	FPM (FKM)	0.6	14613062
DN10	12	M 18x1.5	PN500	Manufacturer standard	Handle	T-bore	FPM (FKM)	FPM (FKM)	0.6	14613063
DN10	12	M 18x1.5	PN500	Manufacturer standard	Handle	T-bore	NBR	NBR	0.6	14288536
DN10	12	M 18x1.5	PN500	Manufacturer standard	Handle	L-bore	NBR	NBR	0.6	14288534
DN13	15	M 22x1.5	PN500	Manufacturer standard	Handle	L-bore	FPM (FKM)	FPM (FKM)	0.7	14613070
DN13	15	M 22x1.5	PN500	Manufacturer standard	Handle	T-bore	FPM (FKM)	FPM (FKM)	0.7	14613071
DN13	15	M 22x1.5	PN500	Manufacturer standard	Handle	T-bore	NBR	NBR	0.7	14288552
DN13	15	M 22x1.5	PN500	Manufacturer standard	Handle	L-bore	NBR	NBR	0.7	14288550
DN13	18	M 26x1.5	PN500	Manufacturer standard	Handle	L-bore	FPM (FKM)	FPM (FKM)	0.7	14613074
DN13	18	M 26x1.5	PN500	Manufacturer standard	Handle	T-bore	FPM (FKM)	FPM (FKM)	0.7	14613075
DN13	18	M 26x1.5	PN500	Manufacturer standard	Handle	T-bore	NBR	NBR	0.7	14288562
DN13	18	M 26x1.5	PN500	Manufacturer standard	Handle	L-bore	NBR	NBR	0.7	14288560
DN20	22	M 30x2	PN315	Manufacturer standard	Handle	L-bore	FPM (FKM)	FPM (FKM)	1.8	14613079
DN20	22	M 30x2	PN315	Manufacturer standard	Handle	T-bore	NBR	NBR	1.8	14288572

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal inner diameter	External tube diameter of connection mm	Connection, gland nut mm	Pressure rating	Face to Face norm	Manual operation	Ball bore	Secondary spindle seal material	Body seal	Weight kg	Article
DN20	22	M 30x2	PN315	Manufacturer standard	Handle	L-bore	NBR	NBR	1.8	14288570
DN25	28	M 36x2	PN315	Manufacturer standard	Handle	L-bore	FPM (FKM)	FPM (FKM)	2.4	14613088
DN25	28	M 36x2	PN315	Manufacturer standard	Handle	T-bore	NBR	NBR	2.4	14613089
DN25	28	M 36x2	PN315	Manufacturer standard	Handle	L-bore	NBR	NBR	2.4	14601668

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.