



VAG Check valve Series: Reto-Stop Type: 21122 Ductile cast iron Flange PN10/16

Characteristics

Series: Reto-Stop

Type: 21122

Norm: EN (DIN)

Construction type: Straight

Housing material: Ductile cast iron

Material quality: EN-JS1030

Surface protection: Epoxy coating (in- and external)

Connection: Flange

Flange finish: Raised face

Face to Face norm: EN 558, Series 48

Maximum medium temperature (continuous): 50 °C

Nominal inner diameter	Pressure rating	Face to Face length mm	Valve shape	Sealing	Material disc	Material cover	Material cover gasket	Minimum medium temperature (continuous) °C	Maximum pressure difference at 20 °C bar	Article
DN40	PN16	180	Swing type	EPDM	EN-JS1030	EN-JS1030	EPDM	-10	16	12674165
DN50	PN16	200	Swing type	EPDM	EN-JS1030	EN-JS1030	EPDM	-10	16	12674166
DN65	PN16	240	Swing type	EPDM	EN-JS1030	EN-JS1030	EPDM	-10	16	12674167
DN80	PN16	260	Swing type	EPDM	EN-JS1030	EN-JS1030	EPDM	-10	16	12674168
DN100	PN16	300	Swing type	EPDM	EN-JS1030	EN-JS1030	EPDM	-10	16	12674169
DN125	PN16	350	Swing type	EPDM	EN-JS1030	EN-JS1030	EPDM	-10	16	12674170
DN150	PN16	400	Swing type	EPDM	EN-JS1030	EN-JS1030	EPDM	-10	16	12674171
DN200	PN10	500	Swing type	EPDM	EN-JS1030	EN-JS1030	EPDM	-10	10	12674173
DN200	PN16	500	Swing type	EPDM	EN-JS1030	EN-JS1030	EPDM	-10	16	12674172
DN250	PN10	600	Swing type	EPDM	EN-JS1030	EN-JS1030	EPDM	-10	10	12642183
DN250	PN16	600	Swing type	EPDM	EN-JS1030	EN-JS1030	EPDM	-10	16	12618669
DN300	PN10	700	Swing type	EPDM	EN-JS1030	EN-JS1030	EPDM	-10	10	12674175
DN300	PN16	700	Swing type	EPDM	EN-JS1030	EN-JS1030	EPDM	-10	16	12674174

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.