



ASCO Solenoid valve 2/2 Type: 32300 Series: 210 Brass Pilot operated hung diaphragm Normally closed (NC)

Characteristics

Series: 210

Type: 32300

Process connection: Internal thread (BSPP)

Function: Normally closed (NC)

Actuation: Pilot operated hung diaphragm

Minimum pressure difference: 0 bar

Electrical connection: Plug EN 175301-803 type A

Max. viscosity: 65 mm²/s

Housing material: Brass

Material coil housing: Epoxy

Material shorting ring: Copper

Working time: 100 %

Level of protection (IP value): IP65

Emergency manual operation: None

Explosion-proof: No


SIL certified: No

Application

- In systems with a small differential pressure or as a drain from a pressureless tank. Neutral gases.
- Neutral liquids.
- Hydraulic oils.
- With FKM/FPM seals suitable for biofuels

Technical Information

- Robust construction.



Size table:

Type	Size	A	B	C	D	E	F	H	Weight
		mm	mm	mm	mm	mm	mm	mm	kg
SCE210B156	1.1/2"	86	56	33	111	50	99	158	2.8
SCE210B155	1.1/4"	86	56	33	95	50	83	148	2
SCE210C094	1/2"	80	50	30	70	45	58	109	0.8
SCE210D095	3/4"	80	50	30	73	45	58	121	1

Maximum pressure difference table

Size	dP ^{min}	dP ^{max} Water		dP ^{max} Gas		dP ^{max} Oil	
		V AC	V DC	V AC	V DC	V AC	V DC
3/8"	0 bar	9 bar	3 bar	9 bar	3 bar	-	-
1/2"	0 bar	9 bar	3 bar	9 bar	3 bar	-	-
3/4"	0 bar	9 bar	3 bar	9 bar	3 bar	-	-
1"	0 bar	9 bar	6 bar	9 bar	6 bar	9 bar	6 bar

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Maximum pressure difference table							
Size	dP ^{min}	dP ^{max} Water		dP ^{max} Gas		dP ^{max} Oil	
		V AC	V DC	V AC	V DC	V AC	V DC
1.1/4"	0 bar	9 bar	6 bar	9 bar	6 bar	9 bar	6 bar
1.1/2"	0 bar	9 bar	5 bar	9 bar	5 bar	9 bar	5 bar

Size process connection	Orifice	Kvs value	Maximum pressure difference	Coil type	Supply voltage	Power	Starting power	Sealing	Membrane material	Article
	mm	m ³ /h	bar							
1.1/2" [40]	32	19.3	9	400525-101	24V AC	15.4 W / 33.6 VA	110 VA	NBR	NBR	11479428
1.1/2" [40]	32	19.3	5	400625-242	24V DC	16.8 W [hot] - 23 W [cold]		NBR	NBR	12159941
1.1/2" [40]	32	19.3	9	400525-117	230V AC	15.4 W / 33.6 VA	110 VA	NBR	NBR	11454515
1.1/4" [32]	28	12.8	9	400525-101	24V AC	15.4 W / 33.6 VA	110 VA	NBR	NBR	11423601
1.1/4" [32]	28	12.8	6	400625-242	24V DC	16.8 W [hot] - 23 W [cold]		NBR	NBR	11352944
1.1/4" [32]	28	12.8	9	400525-117	230V AC	15.4 W / 33.6 VA	110 VA	NBR	NBR	11277282
1/2" [15]	16	3.4	9	400425-101	24V AC	10.5 W / 23 VA	5 VA	NBR	NBR	11399829
1/2" [15]	16	3.4	3	400425-142	24V DC	9 W [hot] - 11.2 W [cold]		NBR	NBR	11341189
1/2" [15]	16	3.4	9	400425-117	230V AC	10.5 W / 23 VA	5 VA	NBR	NBR	11269238
3/4" [20]	19	4.3	9	400425-101	24V AC	10.5 W / 23 VA	5 VA	NBR	NBR	11038619
3/4" [20]	19	4.3	3	400425-142	24V DC	9 W [hot] - 11.2 W [cold]		FPM (FKM)	FPM (FKM)	11620247
3/4" [20]	19	4.3	3	400425-142	24V DC	9 W [hot] - 11.2 W [cold]		NBR	NBR	11342268
3/4" [20]	19	4.3	9	400425-117	230V AC	10.5 W / 23 VA	5 VA	FPM (FKM)	FPM (FKM)	11396100
3/4" [20]	19	4.3	9	400425-117	230V AC	10.5 W / 23 VA	5 VA	NBR	NBR	11207419

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.