

BOSCH REXROTH Ball transfer unit Steel, galvanized Series: R05312

- With plastic load ball
- Particularly suitable for transporting sensitive materials such as glass, polished aluminum, brass and steel
- Load ball made from PA66
- All parts galvanized
- Balls made from corrosion-resistant steel 1.3541 / 1.4034

Characteristics

Series: R0531 2

Housing material: Steel, galvanized

Material ball: PA66

Material cover: Steel, galvanized

Manufacturer ID	Size	Outer diameter of flange	Height	Outer diameter of ball	Diameter, housing	Flange thickness	Working height of ball	Dynamic load rating	Static load rating	Article
		mm	mm	mm	mm	mm	mm	N	N	
KU-C15-P-OFK	15	31	21.5	15.875	24	2.5	9.5	70	70	23550067
KU-C22-P- MFK	22	45	29.3	22.875	36	2.9	9.6	100	100	23550068
KU-C30-P- MFK	30	55	37.3	29.9	45	3.7	13.6	150	150	23550069

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

PR110592327945991_EN_01.07.2024