

## SMC Speed Controller, Standard, Metal Body Elbow Style (metric) series AS\*2/4\*0

Metal body elbow style

Body sizes: M3, M5, 1/8, 1/4, 3/8, 1/2

Meter in or meter out

Port sizes: M3, M5, 10-32UNF, 1/8, 1/4, 3/8, 1/2

## **Characteristics**

Series: AS

Execution: Flow/check valve

**Mounting:** Threaded

Material housing: Brass, Nickel-plated

Seal material: HNBR

Operating pressure: 1 / 10 bar Temperature range: -5 / 60 °C

Fluid: Compressed air in accordance with

ISO8573-1:2010

Port thread type	Pneumatic connection 1	Article
BSPT (R)	1/2	24115561
BSPT (R)	1/8	13661755
BSPT (R)	3/8	24115507
External thread (Metric)	M 3	24115327
External thread (Metric)	M 3	24115365
External thread (Metric)	M 5	24115328

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

E-mail: pneumatiek@eriks.nl

PR1227086996662395\_EN\_30.06.2024