



FLEXION Push in fitting stainless steel AISI 316L elbow male BSPT(R)

Characteristics

Type: SSPL

Material: Stainless steel 316L

Operating temperature: -20 / 180 °C

Operating pressure: -0.99 / 20 bar

Manufacturer ID	Tube Outside Diameter mm	Thread type	Thread size	Article
SSPL4-01-FX	4	External thread BSPT (R)	1/8	14060031
SSPL6-02-FX	6	External thread BSPT (R)	1/4	14060033
SSPL6-01-FX	6	External thread BSPT (R)	1/8	14060032
SSPL8-02-FX	8	External thread BSPT (R)	1/4	14060035
SSPL8-01-FX	8	External thread BSPT (R)	1/8	14060034
SSPL10-02-FX	10	External thread BSPT (R)	1/4	14060036
SSPL10-03-FX	10	External thread BSPT (R)	3/8	14060037
SSPL12-03-FX	12	External thread BSPT (R)	3/8	14060038

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.