



FLEXION Push in fitting stainless steel AISI 316L straight male BSPP(G) and metric

Characteristics

Type: SSPC

Material: Stainless steel 316L

Operating temperature: -20 / 180 °C

Operating pressure: -0.99 / 20 bar

| Manufacturer ID | Tube Outside Diameter mm | Thread type | Thread size | Article |
|-----------------|-----------------------------|--------------------------|-------------|----------|
| SSPC4-M5-FX | 4 | External thread [M] | M 5 | 14059999 |
| SSPC4-G01-FX | 4 | External thread BSPP [G] | 1/8 | 14060000 |
| SSPC6-G02-FX | 6 | External thread BSPP [G] | 1/4 | 14060002 |
| SSPC6-G01-FX | 6 | External thread BSPP [G] | 1/8 | 14060001 |
| SSPC8-G02-FX | 8 | External thread BSPP [G] | 1/4 | 14060004 |
| SSPC8-G01-FX | 8 | External thread BSPP [G] | 1/8 | 14060003 |
| SSPC10-G02-FX | 10 | External thread BSPP [G] | 1/4 | 14060005 |
| SSPC10-G03-FX | 10 | External thread BSPP [G] | 3/8 | 14060006 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.