



FLEXION Push in fitting stainless steel AISI 316L straight male BSPT(R)

Characteristics

Type: SSPC

Material: Stainless steel 316L

Operating temperature: -20 / 180 °C

Operating pressure: -0.99 / 20 bar

Manufacturer ID	Tube Outside Diameter mm	Thread type	Thread size	Article
SSPC4-02-FX	4	External thread BSPT (R)	1/4	14060008
SSPC4-01-FX	4	External thread BSPT (R)	1/8	14060007
SSPC6-02-FX	6	External thread BSPT (R)	1/4	14060010
SSPC6-01-FX	6	External thread BSPT (R)	1/8	14060009
SSPC8-02-FX	8	External thread BSPT (R)	1/4	14060012
SSPC8-01-FX	8	External thread BSPT (R)	1/8	14060011
SSPC10-02-FX	10	External thread BSPT (R)	1/4	14060013
SSPC10-03-FX	10	External thread BSPT (R)	3/8	14060014
SSPC12-04-FX	12	External thread BSPT (R)	1/2	14060016
SSPC12-03-FX	12	External thread BSPT (R)	3/8	14060015

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.