



## FLEXION Push in fitting stainless steel AISI 316L elbow male BSPP(G) and metric

### Characteristics

**Type:** SSPL

**Material:** Stainless steel 316L

**Operating temperature:** -20 / 180 °C

**Operating pressure:** -0.99 / 20 bar

Manufacturer ID	Tube Outside Diameter mm	Thread type	Thread size	Article
SSPL4-M5-FX	4	External thread (M)	M 5	14060017
SSPL4-G01-FX	4	External thread BSPP (G)	1/8	14060018
SSPL6-G02-FX	6	External thread BSPP (G)	1/4	14060020
SSPL6-G01-FX	6	External thread BSPP (G)	1/8	14060019
SSPL8-G02-FX	8	External thread BSPP (G)	1/4	14060022
SSPL8-G01-FX	8	External thread BSPP (G)	1/8	14060021
SSPL10-G02-FX	10	External thread BSPP (G)	1/4	14060023
SSPL10-G03-FX	10	External thread BSPP (G)	3/8	14060024

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.