



FLEXION Push in fitting nickel plated brass male swiveling tee BSPP(G) and metric

Characteristics

Type: MPGT

Material: Brass, Nickel-plated

Operating temperature: -20 / 80 °C

Operating pressure: -0.99 / 18 bar

Manufacturer ID	Tube Outside Diameter mm	Thread type	Thread size	Article
MPGT4-G01-FX	4	External thread BSPP [G]	1/8	14059901
MPGT6-G02-FX	6	External thread BSPP [G]	1/4	14059904
MPGT6-G01-FX	6	External thread BSPP [G]	1/8	14059903
MPGT8-G02-FX	8	External thread BSPP [G]	1/4	14059906
MPGT8-G01-FX	8	External thread BSPP [G]	1/8	14059905
MPGT10-G02-FX	10	External thread BSPP [G]	1/4	14059907
MPGT10-G03-FX	10	External thread BSPP [G]	3/8	14059908
MPGT12-G03-FX	12	External thread BSPP [G]	3/8	14059909

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.