



FLEXION Push in fitting nickel plated brass male swiveling elbow BSPP(G) and metric

Characteristics

Type: MPH

Material: Brass, Nickel-plated

Operating temperature: -20 / 80 °C

Operating pressure: -0.99 / 20 bar

Manufacturer ID	Tube Outside Diameter mm	Thread type	Thread size	Article
MPH4-M5-FX	4	External thread [M]	M 5	14059890
MPH4-G01-FX	4	External thread BSPP [G]	1/8	14059891
MPH6-G02-FX	6	External thread BSPP [G]	1/4	14059893
MPH6-G01-FX	6	External thread BSPP [G]	1/8	14059892
MPH8-G02-FX	8	External thread BSPP [G]	1/4	14059895
MPH8-G01-FX	8	External thread BSPP [G]	1/8	14059894
MPH10-G02-FX	10	External thread BSPP [G]	1/4	14059896
MPH10-G03-FX	10	External thread BSPP [G]	3/8	14059897
MPH12-G04-FX	12	External thread BSPP [G]	1/2	14059899
MPH12-G03-FX	12	External thread BSPP [G]	3/8	14059898

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.