

## FLEXION Push in fitting nickel plated brass bulkhead union metric



Push in fittings made of a materials "MIX", brass and Technopolymer. This line offers a more competitive priced fitting then the whole brass version, without affecting the fitting performance.

### Characteristics

**Type:** EPM

**Material:** PBT

**Operating temperature:** -20 / 80 °C

**Operating pressure:** -0.99 / 18 bar

### Application


- Application : General

### Construction

- Protection Ring: POM
- Gripping ring: Stainless Steel AISI 301
- Body : Brass UNI EN 12164 CW614N – UNI EN 12165 CW617N Nickel Plated
- Seals: NBR
- Release Ring: POM
- Holding Ring: POM

### Approval

- Conformity : SILICONE FREE , RoHS , REACH



Manufacturer ID	Tube Outside Diameter mm	Article
EPM4-FX	4	EPM4-FX
EPM6-FX	6	EPM6-FX
EPM8-FX	8	EPM8-FX
EPM10-FX	10	EPM10-FX
EPM12-FX	12	EPM12-FX
EPM16-FX	16	EPM16-FX

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.