

FLEXION Push in fitting nickel plated brass-PBT straight male BSPT(R)



Push in fittings made of a materials "MIX", brass and Technopolymer. This line offers a more competitive priced fitting then the whole brass version, without affecting the fitting performance.

Characteristics

Type: EPC

Material: PBT

Operating temperature: -20 / 80 °C

Operating pressure: -0.99 / 20 bar

Application

- Application : General

Construction

- Protection Ring: POM
- Gripping ring: Stainless Steel AISI 301
- Body : Brass UNI EN 12164 CW614N – UNI EN 12165 CW617N Nickel Plated
- Seals: NBR
- Release Ring: POM
- Holding Ring: POM

Approval

- Conformity : SILICONE FREE , RoHS , REACH

Manufacturer ID	Tube Outside Diameter mm	Thread type	Thread size	Article
EPC4-02-FX	4	External thread BSPT [R]	1/4	13960464
EPC4-01-FX	4	External thread BSPT [R]	1/8	13960463
EPC6-02-FX	6	External thread BSPT [R]	1/4	14378224
EPC6-01-FX	6	External thread BSPT [R]	1/8	14378223
EPC6-03-FX	6	External thread BSPT [R]	3/8	13960472
EPC8-04-FX	8	External thread BSPT [R]	1/2	14378298
EPC8-02-FX	8	External thread BSPT [R]	1/4	14378222
EPC8-01-FX	8	External thread BSPT [R]	1/8	14378221
EPC8-03-FX	8	External thread BSPT [R]	3/8	14378295
EPC10-04-FX	10	External thread BSPT [R]	1/2	14378220
EPC10-02-FX	10	External thread BSPT [R]	1/4	14378219
EPC10-01-FX	10	External thread BSPT [R]	1/8	13960445
EPC10-03-FX	10	External thread BSPT [R]	3/8	13960447
EPC12-04-FX	12	External thread BSPT [R]	1/2	14378218
EPC12-03-FX	12	External thread BSPT [R]	3/8	14378293
EPC16-04-FX	16	External thread BSPT [R]	1/2	13960459

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.