



FLEXION Push in fitting nickel plated brass-PBT elbow male BSPT(R)

Characteristics

Type: EPL

Material: PBT

Operating temperature: -20 / 70 °C

Operating pressure: -0.99 / 18 bar

Manufacturer ID	Tube Outside Diameter mm	Thread type	Thread size	Article
EPL4-02-FX	4	External thread BSPT (R)	1/4	EPL4-02-FX
EPL4-01-FX	4	External thread BSPT (R)	1/8	EPL4-01-FX
EPL6-04-FX	6	External thread BSPT (R)	1/2	EPL6-04-FX
EPL6-02-FX	6	External thread BSPT (R)	1/4	EPL6-02-FX
EPL6-01-FX	6	External thread BSPT (R)	1/8	EPL6-01-FX
EPL6-03-FX	6	External thread BSPT (R)	3/8	EPL6-03-FX
EPL8-04-FX	8	External thread BSPT (R)	1/2	EPL8-04-FX
EPL8-02-FX	8	External thread BSPT (R)	1/4	EPL8-02-FX
EPL8-01-FX	8	External thread BSPT (R)	1/8	EPL8-01-FX
EPL8-03-FX	8	External thread BSPT (R)	3/8	EPL8-03-FX
EPL10-04-FX	10	External thread BSPT (R)	1/2	EPL10-04-FX
EPL10-02-FX	10	External thread BSPT (R)	1/4	EPL10-02-FX
EPL10-01-FX	10	External thread BSPT (R)	1/8	EPL10-01-FX
EPL10-03-FX	10	External thread BSPT (R)	3/8	EPL10-03-FX
EPL12-04-FX	12	External thread BSPT (R)	1/2	EPL12-04-FX
EPL12-02-FX	12	External thread BSPT (R)	1/4	EPL12-02-FX
EPL12-03-FX	12	External thread BSPT (R)	3/8	EPL12-03-FX
EPL16-04-FX	16	External thread BSPT (R)	1/2	EPL16-04-FX
EPL16-03-FX	16	External thread BSPT (R)	3/8	EPL16-03-FX

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.