

SMC Mechanical Joint Rodless Cylinder, High Precision Guide series MY1H

- Mechanical joint rodless cylinder with high precision guide
- Bore sizes: 16, 20, 25, 32, 40 (mm)
- Strokes up to 1500mm depending upon bore size
- With one or two stroke adjusters with or without shocks
- Variety of switches and a variety of lead wire lengths

Characteristics

Series: MY1H

Function: Double acting

Magnetic: No

| Manufacturer ID | Cushioning | Bore diameter | Stroke length | Port Size | Article |
|-----------------|------------|---------------|---------------|-----------|----------|
| | | mm | mm | mm | |
| | | | | | 24130429 |
| MY1H16G-100 | Adjustable | 16 | 100 | M 5 | 24130424 |
| MY1H16G-400 | Adjustable | 16 | 400 | M 5 | 24130425 |
| MY1H20G-250 | Adjustable | 20 | 250 | M 5 | 24130426 |
| MY1H20G-350 | Adjustable | 20 | 350 | M 5 | 24130427 |
| MY1H20G-400 | Adjustable | 20 | 400 | M 5 | 24130428 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

E-mail: pneumatiek@eriks.be

PR1436360577798_EN_02.06.2024