



## GF 3-way coupling in PVC-U Serie: 510 Glued sleeve/Glued end

### Characteristics

**Series:** 510

**Material:** PVC-U

**Connection:** Glued sleeve

**Connection 2:** Glued end

**Seal material:** FPM (FKM)

**Minimum medium temperature (continuous):** 0 °C

**Maximum medium temperature (continuous):** 60 °C

Shape	External tube diameter of connection	External tube diameter of connection 2	Pressure rating	Article
	mm	mm		
3-piece coupling	16	12	PN16	12450919
3-piece coupling	16		PN16	11318437
3-piece coupling	20		PN16	12449010
3-piece coupling	20	16	PN16	12450920
3-piece coupling	25	20	PN16	12450921
3-piece coupling	25		PN16	11318436
3-piece coupling	32	25	PN16	12449137
3-piece coupling	32		PN16	12449011
3-piece coupling	40	32	PN16	11254495
3-piece coupling	50		PN16	11398881
3-piece coupling	50	40	PN16	12450922
3-piece coupling	63		PN16	11318208
3-piece coupling	63		PN16	11328653
3-piece coupling	63	50	PN16	12450923

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.