

## Ring gauge type 4404



Design: Made of high-quality special gauge steel, completely hardened, unstressed and precision ground, tolerance class 6g. For metric ISO regular threads DIN 13.

Application: For testing threads.

Note: In order to prevent premature breaking away of the thread gear, the first thread gear is ground and removes coarse dirt. Intermediate dimensions and other tolerances available on request.

Design: Made of high-quality special gauge steel, completely hardened, unclamped and precision ground, tolerance class 6g.

Application: For inspecting threads. Thread go plug gauges or ring gauges must be easy to screw onto the test object. Thread no-go plug gauges or ring gauges have few shortened thread turns, and are used to inspect the flank  $\emptyset$ . It should not be possible to screw them onto the test object.

Note:Intermediate dimensions and other tolerances available on request.

Article
W90A-44040100
W90A-44040120
W90A-44040140
W90A-44040160
W90A-44040180
W90A-44040200
W90A-44040220
W90A-44040240
W90A-44040270
W90A-44040030
W90A-44040035
W90A-44040300
W90A-44040040
W90A-44040050
W90A-44040060
W90A-44040080

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.



Page 1/1

PR1444308147712\_EN\_03.07.2024