

Coupling SHLF-HP/EN



Characteristics

Type: SHLF-HP

Type of component: Hose tail coupling

Material: Carbon steel

Connection type: Flange

Hose fitting type: Swivel Flange

Connection termination: ANSI 300

Elbow angle [degr.]: 0 °

Hose tail execution: Serrated, with safety collar

Temperature range [°C]: -40 / 232 °C

Connection termination size	Hose ID (DN)	Maximum operating pressure		Article
		bar	psi	
1/2"	DN12	18	261	12745226
3/4"	DN19	18	261	12745227
1"	DN25	18	261	12745228
1/2"	DN12	18	261	12745229
3/4"	DN19	18	261	12745230
1"	DN25	18	261	12745231
1/2"	DN12	18	261	12745218
3/4"	DN19	18	261	12745219
1"	DN25	18	261	12745220
1/2"	DN12	18	261	12745221
3/4"	DN19	18	261	12745222
1"	DN25	18	261	12745223

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.