

Flange coupling with knurled tailpiece, type SHLF - ANSI



Characteristics

Type of component: Hose tail coupling

Material: Steel

Connection type: Flange

Hose fitting type: Swivel Flange

Connection termination: ANSI 150

Elbow angle [degr.]: 0 °

Hose tail execution: Serrated, with safety collar

Temperature range [°C]: -40 / 100 °C

Connection termination size	Hose ID (DN)	Maximum operating pressure		Article
		bar	psi	
1/2"	DN12	19.6	284	12493619
3/4"	DN19	19.6	284	12493621
1"	DN25	19.6	284	12493622
1.1/4"	DN32	19.6	284	12493623
1.1/2"	DN38	19.6	284	12493624
2"	DN50	19.6	284	12493625
2.1/2"	DN63	19.6	284	12493626
3"	DN75	19.6	284	11118157
4"	DN100	19.6	284	12493628
5"	DN125	19.6	284	12493630
6"	DN150	19.6	284	11080442

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.