



## GF Ball valve Series: 546 PP-H/PE Plastic welded sleeve PN10

### Characteristics

**Series:** 546

**Construction type:** 2-way

**Housing construction:** 3-part

**Housing material:** PP-H/PE

**Connection:** Plastic welded sleeve

**Material ball:** PP-H

**Seat material:** PTFE

**Spindle material:** PP

**Minimum medium temperature (continuous):** 10 °C

**Maximum medium temperature (continuous):** 95 °C

**With drain:** No

Nominal inner diameter	External tube diameter of connection mm	Pressure rating	Face to Face norm	Manual operation	Bore	With locking device	Primary spindle seal material	Secondary spindle seal material	Body seal	Article
DN25	32	PN10	Manufacturer standard	Handle	Full bore		FPM (FKM)	FPM (FKM)	FPM (FKM)	11308610
DN32	40	PN10	Manufacturer standard	Handle	Full bore		EPDM	EPDM	EPDM	11291101
DN40	50	PN10	Manufacturer standard	Handle	Full bore		EPDM	EPDM	EPDM	11291102
DN40	50	PN10	Manufacturer standard	Handle	Full bore		FPM (FKM)	FPM (FKM)	FPM (FKM)	11308609

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.