



Flange coupling with knurled tailpiece, type SHLF/SHFF

Characteristics

Type of component: Hose tail coupling

Material: Steel

Connection type: Flange

Hose fitting type: Fixed flange

Connection termination: ANSI 150

Elbow angle [degr.]: 0 °

Hose tail execution: Serrated, with safety collar

Temperature range [°C]: -40 / 100 °C

Connection termination size	Hose ID (DN)	Maximum operating pressure		Article
		bar	psi	
1/2"	DN12	20	290	12609009
3/4"	DN19	20	290	12609010
1"	DN25	20	290	12609011
1.1/4"	DN32	20	290	12609012
1.1/2"	DN38	20	290	12609013
2"	DN50	20	290	12609014
2.1/2"	DN63	20	290	12609015
3"	DN75	20	290	12609016
4"	DN100	20	290	12609017
5"	DN125	20	290	12609018
6"	DN150	20	290	12609019
1/2"	DN12	20	290	12608998
3/4"	DN19	20	290	12608999
1.1/4"	DN32	20	290	12609001
1.1/2"	DN38	20	290	12609002
2.1/2"	DN63	20	290	12609004
3"	DN75	20	290	12609005
5"	DN125	20	290	12609007
6"	DN150	20	290	12609008

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.