



Hose Abraflex LD EC (Electrical Conductive), light abrasive PU suction & blower hose, Ω



Application

- light suction and blower hose for abrasive solids such as granulates, chips
- good resistance to oil and petrol vapors
- suitable for applications with static electricity

Temperature range

-40 °C to +90 °C

Properties

- polyurethane profile, extremely wear resistant, with a completely embedded steel spiral, thickness polyurethane around 0,8 mm
- smooth tube, corrugated cover
- flow direction is shown by an arrow on the hose
- stays flexible at low temperatures
- plasticiser and halogen-free
- gas and liquid tight
- UV and ozone resistant
- special antistatic PUR [R < 1 k Ω]

Connections

free of choice or to be mounted directly on pipe

Assembly

worm drive clamps type Spiralex or aluminum safety clamps

Options

The Spiralex hose clamp has a "bridge" profile which prevents leakage from under the spiral.

Internal diameter	Wall thickness	Outer diameter	Maximum operating pressure	Minimum burst pressure	Vacuum-resistance at 20 °C	Minimum bending radius	Roll length	Article
mm	mm	mm	bar	bar	%	mm	m	
125	4.5	134	0.8	2.4	28	101	10	12604914
300	4.5	309	0.3	0.9	6	190	10	12470913

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.