



CENTER LINE RS Butterfly valve Type: 714 Ductile cast iron/ Stainless steel Pneumatic operated Double acting Lug type

Characteristics

Type: 714
Norm: EN [DIN]
Valve design: Centric
Housing material: Ductile cast iron
Material quality: EN-JS1030
Surface protection: Epoxy
Connection: Lug type
Standard connection: EN [DIN]
Face to Face norm: EN 558, Series 20
Operation: Pneumatic operated

Characteristics [2]

Operating principle: Double acting
Brand actuator: AMG
Top flange standard: ISO 5211 Direct Mount
Housing lining: Replaceable
Disk material: Stainless steel
Quality class disc: 1.4408
Actuator material: Aluminium

Nominal inner diameter	Pressure rating	Pressure rating flange	Face to Face length mm	Type coding actuator	Material liner	Minimum medium temperature (continuous) °C	Maximum medium temperature (continuous) °C	Article
DN50	PN10	PN10/16	43	SAD10	EPDM	-10	120	10056668
DN65	PN10	PN10/16	46	SAD10	EPDM	-10	120	10056669
DN80	PN10	PN10/16	46	SAD15	EPDM	-10	120	10056670
DN100	PN10	PN10/16	52	SAD15	EPDM	-10	120	10056671
DN125	PN10	PN10/16	56	SAD20	EPDM	-10	120	10056672
DN150	PN10	PN10/16	56	SAD25	EPDM	-10	120	10056673
DN200	PN10	PN10	60	SAD25	EPDM	-10	120	10056674
DN250	PN10	PN10	68	SAD30	EPDM	-10	120	10056675
DN300	PN10	PN10	78	SAD33	EPDM	-10	120	10056676

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.