



AKATHERM Centric reducer PE-100 SDR17 Plastic welded end

Characteristics

Centric: Yes

Material: PE-100

Connection: Plastic welded end

Suited for electrofusion fitting: No

Minimum medium temperature (continuous): -20 °C

Maximum medium temperature (continuous): 45 °C

Shape	External tube diameter of connection mm	External tube diameter of connection 2 mm	Pressure rating	Article
Reduction piece	63	50	PN10	10044742
Reduction piece	75	50	PN10	10044744
Reduction piece	75	63	PN10	10044745
Reduction piece	90	63	PN10	10044747
Reduction piece	90	75	PN10	10044748
Reduction piece	90	50	PN10	10044746
Reduction piece	110	75	PN10	10044751
Reduction piece	110	50	PN10	10044749
Reduction piece	110	63	PN10	10044750
Reduction piece	110	90	PN10	10044752
Reduction piece	125	90	PN10	11062173
Reduction piece	125	110	PN10	11209164
Reduction piece	140	125	PN10	11242928
Reduction piece	140	90	PN10	11138434
Reduction piece	140	75	PN10	11053818
Reduction piece	140	110	PN10	10044753
Reduction piece	160	110	PN10	11138473
Reduction piece	160	90	PN10	10044754
Reduction piece	160	140	PN10	11062012
Reduction piece	160	125	PN10	11242929
Reduction piece	180	125	PN10	11242930
Reduction piece	180	90	PN10	11067407
Reduction piece	200	140	PN10	10044755
Reduction piece	225	160	PN10	11242931
Reduction piece	225	180	PN10	11010540
Reduction piece	225	200	PN10	11244281
Reduction piece	250	160	PN10	11242932
Reduction piece	250	200	PN10	11244294
Reduction piece	315	225	PN10	10044756

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.