

## AKATHERM Centric reducer PE-100 SDR11 - mirror weld



### Characteristics

**Centric:** Yes

**Material:** PE-100

**Connection:** Plastic welded end

**Suited for electrofusion fitting:** No

**Minimum medium temperature (continuous):** -20 °C

**Maximum medium temperature (continuous):** 45 °C

Shape	External tube diameter of connection mm	External tube diameter of connection 2 mm	Pressure rating	Article
Reduction piece	25	20	PN16	11246092
Reduction piece	32	20	PN16	11246273
Reduction piece	32	25	PN16	11246274
Reduction piece	40	20	PN16	11246275
Reduction piece	40	32	PN16	11246277
Reduction piece	50	40	PN16	11246279
Reduction piece	50	32	PN16	11246278
Reduction piece	63	32	PN16	11246280
Reduction piece	63	50	PN16	11246282
Reduction piece	63	40	PN16	11246281
Reduction piece	75	50	PN16	11246283
Reduction piece	75	63	PN16	11246284
Reduction piece	90	75	PN16	11246286
Reduction piece	90	63	PN16	11246285
Reduction piece	110	63	PN16	11246287
Reduction piece	110	75	PN16	11246288
Reduction piece	110	90	PN16	11246289
Reduction piece	125	90	PN16	11246291
Reduction piece	125	63	PN16	11246290
Reduction piece	125	110	PN16	11246292
Reduction piece	160	110	PN16	11246293
Reduction piece	160	125	PN16	11246294
Reduction piece	200	160	PN16	11246295
Reduction piece	225	160	PN16	11246296

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.