


JC Ball valve Series: 41501RLICG Type: 3326 Steel Fire safe Internal thread (NPT) Class 1500



Characteristics

Series: 41501RLICG
Type: 3326
Norm: ASME
Construction type: 2-way
Housing construction: 1-part
Housing material: Steel
Material quality: ASTM A350 LF2
Connection: Internal thread (NPT)
Spindle material: 1.4006
Primary spindle seal material: RPTFE

Secondary spindle seal material: FPM (FKM)
Tertiary spindle seal material: Graphite
Actuator material: Ductile cast iron
Maximum medium temperature (continuous): 260 °C
Fire safe: Yes

Application

- Recommended in: Chemical

Nominal inner diameter	Standard thread connection	Pressure rating	Face to Face norm	Manual operation	Bore	Material ball	Seat material	Body seal	Minimum medium temperature (continuous) °C	Article
1/2" [15]	ASME B1.20.1	Class 1500	Manufacturer standard	Handle	Full bore	ASTM A351 CF8M	RPTFE	PTFE/Graphite	-46	11604296
3/4" [20]	ASME B1.20.1	Class 1500	Manufacturer standard	Handle	Full bore	ASTM A351 CF8M	RPTFE	PTFE/Graphite	-46	11603904
1" [25]	ASME B1.20.1	Class 1500	Manufacturer standard	Handle	Full bore	ASTM A351 CF8M	RPTFE	Graphite	-46	11604297
1.1/2" [40]	ASME B1.20.1	Class 1500	Manufacturer standard	Handle	Full bore	ASTM A351 CF8M	RPTFE	PTFE/Graphite	-50	11606891
2" [50]	ASME B1.20.1	Class 1500	Manufacturer standard	Handle	Full bore	ASTM A351 CF8M	RPTFE	PTFE/Graphite	-46	11604298

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.