



Rubber sheet CR/SBR 70 NEOPRENE 131201

Characteristics

Series: CR/SBR 70

Type: NEOPRENE

Max. pressure: 10 bar

Colour: Black

Temperature range: -20 / 100 °C

Suitable for medium: Alkalies, Weak Alkalies, Water
[process water], Weak Acids, Water, Air
[compressed air]

Thickness mm	Length mm	Width mm	Number of inserts	Article
1	20000	1400		10017148
1.5	15000	1400		10017149
1.5	15000	1400	1	10017160
2	15000	1400		10017150
2	15000	1400	1	10017161
3	10000	1400	2	10017163
3	10000	1400		10017151
3	10000	1400	1	10017162
4	10000	1400		10017152
5	10000	1400	2	10017164
5	10000	1400		10017153
6	10000	1400		10017154
8	5000	1400	2	10017165
8	5000	1400		10017155
10	5000	1400		10017156
12	5000	1400		10017157
15	5000	1400		10017158
20	2500	1400		10017159

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.