

ECON® Temperature sensor fig. 30205 Pt100 stainless steel connection head

Characteristics

Type: 30205
Type of connection head: Stainless steel Bajonet head
Accuracy class: Class B IEC 60751
With display: No
With pocket tube: No
Sensor diameter: 8 mm
Process connection material: Stainless steel 316L
Material connection head: Stainless steel 304

Characteristics [2]

Material cable screw gland: Plastic
Sensor material: Stainless steel 316L
Electrical connection: Cable screw gland
Level of protection [IP value]: IP65
Ambient temperature: -40 / 80 °C



L	a	b	c	d	e	f	G	h	SW
mm	mm	mm	mm	Ø mm	mm				
50	64	51	40	8	12	10	1/2"	- / 28	27
100	64	51	40	8	12	10	1/2"	- / 28	27
150	64	51	40	8	12	10	1/2"	- / 28	27
200	64	51	40	8	12	10	1/2"	- / 28	27

Measuring element	Measuring insert	Measuring range °C	Process connection	Size process connection	With neck	Insert length mm	Article
Pt100 3 wires	Not replaceable	-50 / 200	External thread	1/2" BSPP[G]	Yes	50	13674100
Pt100 3 wires	Not replaceable	-50 / 200	External thread	1/2" BSPP[G]	Yes	100	13674101
Pt100 3 wires	Not replaceable	-50 / 200	External thread	1/2" BSPP[G]	Yes	150	13674102
Pt100 3 wires	Not replaceable	-50 / 200	External thread	1/2" BSPP[G]	Yes	200	13674104

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.