

GOODALL Coupling GDF-W-C



Characteristics

Type of component: Hose tail coupling

Material: AISI 316

Connection type: Welding coupling

Hose fitting type: Weld

Connection termination: Welded end

Elbow angle [degr.]: 0 °

Hose tail execution: Serrated, with safety collar

Temperature range [°C]: -30 / 260 °C

Connection termination size	Hose ID (DN)	Maximum operating pressure		Article
		bar	psi	
19,0x1,5 [16,0]	DN12	40	580	13704472
23,0x1,5 [20,0]	DN19	40	580	13704473
25,0x1.25 [25.5]	DN25	25	362	13704474
29,0x1,5 [26,0]	DN25	40	580	13704475
35,0x1.5 [32,0]	DN32	40	580	13704477
32,0x1.25 [29.5]	DN32	40	580	13704476
41,0x1,5 [38,0]	DN38	40	580	13704479
38,0x1.25 [35.5]	DN38	40	580	13704478
53,0x1,5 [50,0]	DN50	25	362	13704481
51,0x1.25 [48.5]	DN50	25	362	13704480
63,5x1.5 [60.5]	DN63	25	362	13704482
73,0x3,0 [67,0]	DN63	25	362	13704483
85,0x2,0 [81,0]	DN75	25	362	13704485
76,0x2,0 [72,0]	DN75	25	362	13704484
106,0x3,0 [100,0]	DN100	25	362	13704487
101,6x2,0 [99.6]	DN100	25	362	13704486

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.