

ECON® Ball valve Type: 7288 Stainless steel Fire safe Flange PN16/40









Characteristics

Type: 7288 Norm: EN (DIN)

Construction type: 2-way
Housing construction: 2-part
Housing material: Stainless steel

Material quality: 1.4408 Connection: Flange Flange finish: Raised face

Top flange standard: ISO 5211 Direct Mount

Seat material: TFM 1600 **Spindle material:** 1.4401

Primary spindle seal material: PTFE

Secondary spindle seal material: FPM (FKM)
Tertiary spindle seal material: Graphite
Body seal: SWG 316L/PTFE/Graphite

Fire safe: Yes

Application

- Industrial applications up to 16 or 40 bar.
- Liquid and gaseous media.
- Recommended in: Food & Beverages

Technical Information

- Flanged connection in accordance with EN1092-1.
- Floating ball.
- Pressure rating PN16 or PN40.
- With direct-mount top flange in accordance with ISO 5211.
- All components intended to come into contact with food comply with EC 1935.
- Media temperature: -29/+200°C.
- DN15 to DN80 with lever and locking device.
- DN100 with T-bar.

FRIKS BV

Construction

- Two-piece housing construction.
- Design according to EN 12516-1.
- Full bore.
- Equipped with anti-static design between ball and housing.
- Face-to-face dimension according to EN 558, series
 1 (DIN3202-F1).

Approval

- Fire-safe approval in accordance with ISO 10497 and API 607, sixth edition.
- Safety integrity level IEC 61508 SIL 2.
- Declaration of conformity according to EC 1935/2004.
- Fugitive emission certified in accordance with TA-Luft VDI 2440 / VDI 3479.
- Fugitive emission certified in accordance with ISO 15848-1 BH-CO1 and CH-CO3.

Options

- Equipped with worm gearbox and pneumatic, electric or hydraulic actuators.
- Position feedback for manually actuated or automated valves.
- Available with seats in TF4215.
- Stainless steel extended spindle type 8007 for insulation.





Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.



Page 1/2

Ball Valves | Ball valves with flange connection





Size table:

DN	d	L	Н	М
	mm	mm	mm	mm
DN15	15	130	79	145
DN20	20	150	84	145
DN25	25	160	91	175
DN32	32	180	103	175
DN40	38	200	111	194
DN50	50	230	120	194
DN65	63.5	290	150	265
DN80	76	310	160	265
DN100	100	350	182	400
DN50 DN65 DN80	50 63.5 76	230 290 310	120 150 160	194 265 265

Pressure and temperature range								
DN	Pressure rating	-10	50	100	150	200	[°C]	
DN15-DN50	PN40	39	37	33	30	19	[bar]	
DN65-DN100	PN16	16	15	13	13	11	[bar]	

Nominal inner diameter	Pressure rating	Face to Face norm	Manual operation	Mounting flange	Mounting flange 2	Bore	With locking device	Material ball	Actuator material	Article
DN15	PN40	EN 558, Series 1	Handle	F03	F04	Full bore	Yes	1.4408	1.4301	13641961
DN20	PN40	EN 558, Series 1	Handle	F03	F04	Full bore	Yes	1.4408	1.4301	13641977
DN25	PN40	EN 558, Series 1	Handle	F04	F05	Full bore	Yes	1.4408	1.4301	13641809
DN32	PN40	EN 558, Series 1	Handle	F04	F05	Full bore	Yes	1.4408	1.4301	13641978
DN40	PN40	EN 558, Series 1	Handle	F05	F07	Full bore	Yes	1.4408	1.4301	13641956
DN50	PN40	EN 558, Series 1	Handle	F05	F07	Full bore	Yes	1.4408	1.4301	14029631
DN65	PN16	EN 558, Series 1	Handle	F07	F10	Full bore	Yes	1.4408	1.4301	13641957
DN80	PN16	EN 558, Series 1	Handle	F07	F10	Full bore	Yes	1.4408	1.4301	13641976
DN100	PN16	EN 558, Series 1	T-wrench	F10		Full bore	No	1.4408	Steel, galvanized	13642021

e or e advice.
Page 2/2
PKI279278034902869_EN_03.06.2024 Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

E-mail: vk@eriks.nl