

Globe valve Type: 269ZS Cast iron Flange PN16


Characteristics

Type: 269ZS Norm: EN [DIN] Construction type: Angle pattern Housing material: Cast iron Surface protection: Standard manufacturers coating Connection: Flange Flange finish: Raised face Self-locking: Yes Stem seal type: Gland seal Spindle material: CW710R Primary spindle seal material: Graphite

Characteristics (2)

Material bonnet: EN-JL1040 Bonnet gasket material: Graphite Actuator material: Steel Minimum medium temperature (continuous): -10 °C Maximum medium temperature (continuous): 180 °C Maximum pressure difference at 20 °C: 16 bar





DN	А	Н	L	М	Weight	
[mm]	[mm]	[mm]	[mm]	[mm]	[kg]	
15	95	155	90	265	5	
20	105	150	95	265	5.5	
25	115	155	100	265	7	
32	140	160	105	265	8	
40	150	205	115	265	12	
50	165	205	125	265	14	
65	185	210	145	265	20	
80	200	240	155	400	25	
100	220	260	175	400	38	

Pressure and temperature range						
	-10/120 °C	180 °C				
PN16	16	10	[bar]			

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice.

PR1579278036790955_EN_02.06.2024

Page 1/2

ERIKS shall never be liable for damage resulting from the use of the information provided.



Globe Valves | Globe Valves with Flange Connection

Material quality	Nominal inner diameter	Pressure rating	Face to Face norm	Face to Face length	Operation	Type of disc	Type of bonnet	Sealing	Material disc	Article
				mm						
EN-JL1040	DN15	PN16	EN 558, Series 8	90	Lever with counter weight	Fixed disc	Bolted bonnet	Bronze	CC491K (RG5)	13686826
EN-JL1040	DN20	PN16	EN 558, Series 8	95	Lever with counter weight	Fixed disc	Bolted bonnet	Bronze	CC491K (RG5)	13686827
EN-JL1040	DN25	PN16	EN 558, Series 8	100	Lever with counter weight	Fixed disc	Bolted bonnet	Bronze	CC491K (RG5)	13686828
EN-JL1040	DN32	PN16	EN 558, Series 8	105	Lever with counter weight	Fixed disc	Bolted bonnet	Bronze	CC491K (RG5)	13686829
EN-JL1040	DN40	PN16	EN 558, Series 8	115	Lever with counter weight	Fixed disc	Bolted bonnet	Bronze	CC491K (RG5)	13686830
EN-JL1040	DN50	PN16	EN 558, Series 8	125	Lever with counter weight	Fixed disc	Bolted bonnet	Bronze	CC491K (RG5)	13686831
EN-JL1040	DN65	PN16	EN 558, Series 8	145	Lever with counter weight	Fixed disc	Bolted bonnet	Bronze	CC491K (RG5)	13686832
EN-JL1040	DN80	PN16	EN 558, Series 8	155	Lever with counter weight	Fixed disc	Bolted bonnet	Bronze	CC491K (RG5)	13686833
EN-JL1040	DN100	PN16	EN 558, Series 8	175	Lever with counter weight	Fixed disc	Bolted bonnet	Bronze	CC491K (RG5)	13686834

e or e advice. Bris792780367909555_EN_02.06.2024 Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

