



ECON® Globe valve Type: 251 Bronze Internal thread (BSPP) PN25

Bronze globe valve, with PTFE sealing, fixed or loose (SDNR) disc and BSP thread ends, pressure class PN25.



Characteristics

- Type:** 251
- Norm:** EN (DIN)
- Construction type:** Straight
- Housing material:** Bronze
- Connection:** Internal thread (BSPP)
- Standard thread connection:** ISO 228-1
- Stem seal type:** Gland seal
- Material disc:** CC491K (RG5)
- Spindle material:** CuZn35Ni (SoMs59)
- Primary spindle seal material:** Graphite
- Material bonnet:** CC491K (RG5)
- Bonnet gasket material:** PTFE
- Actuator material:** Cast iron
- Minimum medium temperature (continuous):** -10 °C
- Maximum medium temperature (continuous):** 200 °C
- Maximum pressure difference at 20 °C:** 25 bar

Application

- General Industry.
- On board ships (maritime).
- HVAC applications.
- Neutral liquids and gases.
- Steam (max. 6 bar), condensate, hot or cold water, oil (for thermal oil: bellows sealed valve), etc.
- Recommended in: Utilities

Technical Information

- Testing: EN 12266-1.
- Screwed bonnet with secured nut.

Options

- Available including inspection and certification by all leading Classification societies.

DN [mm]	D BSP	H [mm]	L [mm]	ØM [mm]	Weight [kg]
8	1/4"	107	60	63	0.05
10	3/8"	107	60	63	0.5
15	1/2"	107	65	63	0.7
20	3/4"	121	75	80	1
25	1"	131	90	80	1.4
32	1.1/4"	141	105	90	2
40	1.1/2"	151	120	100	2.7
50	2"	168	145	125	4.4

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Globe Valves | Globe Valves with Threaded Connection

Pressure and temperature range					
-10	0	120	180		[°C]
25	25	25	11.3		[bar]

Material quality	Nominal inner diameter	Pressure rating	Face to Face norm	Face to Face length	Operation	Type of disc	Type of bonnet	Sealing	Kv value	Article
				mm					m³/h	
CC491K (RG5)	1/4" [8]	PN25	Manufacturer standard	60	Hand wheel, rising with rising stem	Fixed disc	Screwed and gland nut	PTFE	2.9	14028270
CC491K (RG5)	1/4" [8]	PN25	Manufacturer standard	60	Hand wheel, rising with rising stem	Screw down non-return disc without spring	Screwed and gland nut	PTFE	2.9	14028290
CC491K (RG5)	3/8" [10]	PN25	Manufacturer standard	60	Hand wheel, rising with rising stem	Fixed disc	Screwed and gland nut	PTFE	2.9	14028272
CC491K (RG5)	3/8" [10]	PN25	Manufacturer standard	60	Hand wheel, rising with rising stem	Screw down non-return disc without spring	Screwed and gland nut	PTFE	2.9	14028291
CC491K (RG5)	1/2" [15]	PN25	Manufacturer standard	65	Hand wheel, rising with rising stem	Fixed disc	Screwed and gland nut	PTFE	6.2	14028283
CC491K (RG5)	1/2" [15]	PN25	Manufacturer standard	65	Hand wheel, rising with rising stem	Screw down non-return disc without spring	Screwed and gland nut	PTFE	6.2	14028292
CC491K (RG5)	3/4" [20]	PN25	Manufacturer standard	75	Hand wheel, rising with rising stem	Fixed disc	Screwed and gland nut	PTFE	9.5	14028284
CC491K (RG5)	3/4" [20]	PN25	Manufacturer standard	75	Hand wheel, rising with rising stem	Screw down non-return disc without spring	Screwed and gland nut	PTFE	9.5	14028293
CC491K (RG5)	1" [25]	PN25	Manufacturer standard	90	Hand wheel, rising with rising stem	Fixed disc	Screwed and gland nut	PTFE	17.8	14028285
CC491K (RG5)	1" [25]	PN25	Manufacturer standard	90	Hand wheel, rising with rising stem	Screw down non-return disc without spring	Screwed and gland nut	PTFE	17.8	14028294
CC491K (RG5)	1.1/4" [32]	PN25	Manufacturer standard	105	Hand wheel, rising with rising stem	Fixed disc	Screwed and gland nut	PTFE	21	14028287
CC491K (RG5)	1.1/4" [32]	PN25	Manufacturer standard	105	Hand wheel, rising with rising stem	Screw down non-return disc without spring	Screwed and gland nut	PTFE	21	14028295
CC491K (RG5)	1.1/2" [40]	PN25	Manufacturer standard	120	Hand wheel, rising with rising stem	Fixed disc	Screwed and gland nut	PTFE	35	14028288
CC491K (RG5)	1.1/2" [40]	PN25	Manufacturer standard	120	Hand wheel, rising with rising stem	Screw down non-return disc without spring	Screwed and gland nut	PTFE	35	14028296
CC491K (RG5)	2" [50]	PN25	Manufacturer standard	145	Hand wheel, rising with rising stem	Fixed disc	Screwed and gland nut	PTFE	42	14028289
CC491K (RG5)	2" [50]	PN25	Manufacturer standard	145	Hand wheel, rising with rising stem	Screw down non-return disc without spring	Screwed and gland nut	PTFE	42	14028297

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.