

JALAS Safety shoe JALAS®1538 TERRA S3

Properties

Highest level of protection, excellent grip, perfect fit, extra Comfortable, excellent shock absorption **Specification**

Type of shoe safety footwear, low shoes Nail protection material steel Fitting wide Size range (eu) 35-50 Collection gran premio Platform enduro Upper material pu-coated leather Upper material thickness 1,6-1,8 Pronose material pu Toecap material aluminium Lining material polyester, polyamide Sole material pu midsole, rubber outsole Insole fx2 pro Insole material textile, soft eva, polyester-based Conductive thread, double shock absorption zones in poron®Xrd®

Characteristics

Safety class: S3

Technical Information

Outsole

- Perbunan Athletic ESD, slate grey
- Outsole with 3.8 mm profile
- With increased protection against kinking, reduces lever arms
- Supports the natural motion sequence
- Light and flexible
- Very good abrasion resistance and slip resistance
- Heat resistant up to approx. 220° C

Options

Order information

• Width S and XXB available on request. Please refer to the size table in the appendix to determine your shoe size and width.

Protection class occupational shoes	ОВ	01	O2	О3	04	O5
Protective toecap						
Energy absorption in heel		*	*	*	*	*
Fully enclosed heel		*	*	*	*	*
Antistatic properties		*	*	*		
Puncture resistant outsole				*		
Water penetration and absorption protection			*	*	*	*

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

PR1579278038980508_EN_30.06.2024

Foot Protection | Boots and shoes

Protection class occupational shoes	ОВ	01	C	02	O3	04	O5
Water resistant							
Protection class							
safety shoes	SB	S1	S1P	S2	S3	\$4	S5
Protective toecap	*	*	*	*	*	*	*
Energy absorption in heel		*	*	*	*	*	*
Fully enclosed heel		*	*	*	*	*	*
Antistatic properties		*	*	*	*	*	*
Puncture resistant outsole			*		*		*
Water penetration and absorption protection				*	*	*	*
Water resistant						*	*
Description				Article			

Description	Article
Safety shoe - low cut 1538 TERRA Size 35	14620767
Safety shoe - low cut 1538 TERRA Size 41	14620773
Safety shoe - low cut 1538 TERRA Size 45	14620776
Safety shoe - low cut 1538 TERRA Size 39	14620771
Safety shoe - low cut 1538 TERRA Size 44	14620775
Safety shoe - low cut 1538 TERRA Size 47	14620778
Safety shoe - low cut 1538 TERRA Size 40	14620772
Safety shoe - low cut 1538 TERRA Size 46	14620777
Safety shoe - low cut 1538 TERRA Size 49	14620780
Safety shoe - low cut 1538 TERRA Size 50	14620781
Safety shoe - low cut 1538 TERRA Size 36	14620768
Safety shoe - low cut 1538 TERRA Size 38	14620770
Safety shoe - low cut 1538 TERRA Size 37	14620769
Safety shoe - low cut 1538 TERRA Size 48	14620779
Safety shoe - low cut 1538 TERRA Size 42	14620774
Safety shoe - low cut 1538 TERRA Size 43	13460740

e or e advice. Page 2/2 Page 2/2 Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ${\it ERIKS shall never be liable for damage resulting from the use of the information provided.}\\$

| E-mail: gereedschappen@eriks.nl