

ECON® Cylinder for SOS valve Type: 100X Brass

Brass actuating cylinder for operating the ESD valves.



Characteristics

Type: 100X

Material: Brass

Application

- Activates the closing action of the ESD valve from a mechanical, hydraulic or pneumatic signal.

Technical Information

There are 4 versions:

- Cylinder for mechanical signal for valves DN15 to DN200.
- Cylinder for pneumatic signal for valves DN15 to DN80 or hydraulic signal for valves DN15 to DN200.
- Cylinder for pneumatic signal for valves DN100 to DN200.
- Cylinder for hydraulic signal for valves DN15 to DN200, if impulse unit is placed lower than the valve.

Execution	Suitable for size	Article
Cylinder	Hydraulic DN15-DN200	13463293
Cylinder	Mechanic DN15-DN200	13457259
Cylinder	Pneumatic DN15-DN80, hydraulic DN15-DN200	12707716
Cylinder	Pneumatic DN100-DN200	13463271

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.