



FESTO Electric cylinder unit EPCE

Characteristics

Series: EPCE

Type: Simplified Motion

Housing material: Wrought aluminium alloy,
anodized

Operating temperature: 0 / 50 °C

Manufacturer ID	Construction size	Stroke length		Article
		mm		
EPCE-TB-45-10-FL-ST-M-H1-PLK-AA	45	10		14086285
EPCE-TB-45-20-FL-MF-ST-M-H1-PLK-AA	45	20		14086781
EPCE-TB-45-20-FL-ST-M-H1-PLK-AA	45	20		14086286
EPCE-TB-45-30-FL-ST-M-H1-PLK-AA	45	30		14086780
EPCE-TB-45-30-FL-MF-ST-M-H1-PLK-AA	45	30		14086782
EPCE-TB-45-50-FL-MF-ST-M-H1-PLK-AA	45	50		14086783
EPCE-TB-45-50-FL-ST-M-H1-PLK-AA	45	50		14086287
EPCE-TB-60-10-FL-ST-M-H1-PLK-AA	60	10		14086288
EPCE-TB-60-10-FL-MF-ST-M-H1-PLK-AA	60	10		14086291
EPCE-TB-60-20-FL-MF-ST-M-H1-PLK-AA	60	20		14086292
EPCE-TB-60-20-FL-ST-M-H1-PLK-AA	60	20		14086289
EPCE-TB-60-30-FL-ST-M-H1-PLK-AA	60	30		14086290
EPCE-TB-60-30-FL-MF-ST-M-H1-PLK-AA	60	30		14086294
EPCE-TB-60-50-FL-MF-ST-M-H1-PLK-AA	60	50		14086295
EPCE-TB-60-50-FL-ST-M-H1-PLK-AA	60	50		14086293
EPCE-TB-60-80-FL-ST-M-H1-PLK-AA	60	80		14086297
EPCE-TB-60-80-FL-MF-ST-M-H1-PLK-AA	60	80		14086298

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.