



ASCO Dust collector pulse valve valve 2/2 Type: 32230K series 353 aluminium

Characteristics

Series: 353
Type: 32230K
Function: Normally closed (NC)
Actuation: Indirect-acting
Maximum pressure difference: 8.5 bar
Electrical connection: Plug EN 175301-803 type B
Housing material: Aluminium
Sealing: NBR
Material coil housing: Steel epoxy coating
Material shorting ring: Copper
Membrane material: TPE
Working time: 10 % max. on 1 minute time
Level of protection (IP value): IP66/IP67
Explosion-proof: Yes

Medium temperature: From -20 °C to 140°C

Application

- Pulse valve for blowing through filter bags in dust filter systems.

Technical Information

- On-site control with integrated control valve.
- High flow capacity and short response time.
- Built-in sound absorber.
- Conversion from AC to DC coil possible.

Size process connection	Process connection	Orifice	Kvs value	Minimum pressure difference	Supply voltage	Power	Ex-class	ATEX Zone	Ambient temperature	Article
		mm	m ³ /h	bar						
1.1/2" [40]	Internal thread (BSPP)	55	49	2	24V DC	22 W			From -20 °C to 75 °C	14379335
1.1/2" [40]	Internal thread (BSPP)	55	49	2	230V AC	6,3 W			From -20 °C to 75 °C	14379334
1" [25]	Internal thread (BSPP)	32	20	2	24V AC	6,3 W			From -20 to 85 °C	14105778
1" [25]	Internal thread (BSPP)	32	20	2	24V DC	22 W			From -10 °C to 75 °C	14105786
1" [25]	Quick Coupling	32	20	2	24V DC	22 W			From -20 °C to 75 °C	14105797
1" [25]	Internal thread (BSPP)	32	20	2	24V DC	22 W	II 3GD Ex ec IIC T6-T4 Gc, Ex tc IIIC T110 °C Dc	Zone 2 / 22	From -10 °C to 60 °C	14106146
1" [25]	Internal thread (BSPP)	32	20	2	115V AC	6,3 W			From -20 °C to 75 °C	14105779
1" [25]	Internal thread (BSPP)	32	20	2	230V AC	6,3 W			From -20 °C to 75 °C	14105789
3/4" [20]	Internal thread (BSPP)	32	13	2	24V AC	6,3 W			From -20 °C to 75 °C	14063685
3/4" [20]	Internal thread (BSPP)	32	13	2	24V DC	22 W			From -10 °C to 75 °C	14105784
3/4" [20]	Internal thread (BSPP)	32	20	2	24V DC	10,5 W	II 2GD Ex e mb IIC Gb T3 / Ex tb IIIC T200 °C Db	Zone 1 / 21	From -20 °C to 40 °C	14379614
3/4" [20]	Internal thread (BSPP)	32	13	2	24V DC	22 W	II 3GD Ex ec IIC T6-T4 Gc, Ex tc IIIC T110 °C Dc	Zone 2 / 22	From -10 °C to 60 °C	14105781
3/4" [20]	Internal thread (BSPP)	32	13	2	230V AC	6,3 W			From -20 °C to 75 °C	13715652

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.