



ASAHI Butterfly valve Series: 57 Type: 3742EE PVC-U/PVC-U Electric operated Wafer type

Characteristics

Series: 57
Type: 3742EE
Norm: EN (DIN)
Valve design: Centric
Housing material: PVC-U
Connection: Wafer type
Face to Face norm: Manufacturer standard
Operation: Electric operated
Brand actuator: ECON
Housing lining: Not replaceable

Disk material: PVC-U

Primary spindle seal material: FPM (FKM)

Actuator material: Aluminium

Maximum medium temperature (continuous): 50 °C

Application

- Recommended in: Chemical

Nominal inner diameter	Pressure rating	Pressure rating flange	Face to Face length mm	Type coding actuator	Supply voltage	Material liner	Spindle material	Quality class spindle	Minimum medium temperature (continuous) °C	Article
DN40	PN10	PN10	39	ELA60	24V DC	EPDM	Stainless steel	1.4401	0	14081818
DN40	PN10	PN10	39	ELA60	230 V AC	EPDM	Stainless steel	1.4401	0	14081807
DN40	PN10	PN10	39	ELA60	230 V AC	FPM (FKM)	Stainless steel	1.4401	0	14081826
DN40	PN10	PN10	39	ELA60	24V DC	FPM (FKM)	Stainless steel	1.4401	0	14081837
DN50	PN10	PN10	42	ELA60	24V DC	EPDM	Stainless steel	1.4401	0	14081819
DN50	PN10	PN10	42	ELA60	230 V AC	EPDM	Stainless steel	1.4401	0	14081808
DN50	PN10	PN10	42	ELA60	24V DC	FPM (FKM)	Stainless steel	1.4401	0	14081838
DN50	PN10	PN10	42	ELA60	230 V AC	FPM (FKM)	Stainless steel	1.4401	0	14081827
DN65	PN10	PN10	46	ELA60	230 V AC	EPDM	Stainless steel	1.4401	0	14081809
DN65	PN10	PN10	46	ELA60	24V DC	EPDM	Stainless steel	1.4401	0	14081820
DN65	PN10	PN10	46	ELA60	24V DC	FPM (FKM)	Stainless steel	1.4401	0	14081839
DN65	PN10	PN10	46	ELA60	230 V AC	FPM (FKM)	Stainless steel	1.4401	0	14081828
DN80	PN10	PN10	46	ELA60	24V DC	EPDM	Stainless steel	1.4401	0	14081821
DN80	PN10	PN10	46	ELA60	230 V AC	EPDM	Stainless steel	1.4401	0	14081810
DN80	PN10	PN10	46	ELA60	230 V AC	FPM (FKM)	Stainless steel	1.4401	0	14081829
DN80	PN10	PN10	46	ELA60	24V DC	FPM (FKM)	Stainless steel	1.4401	0	14081840
DN100	PN10	PN10	56	ELA60	230 V AC	EPDM	Stainless steel	1.4401	0	14081811
DN100	PN10	PN10	56	ELA60	24V DC	EPDM	Stainless steel	1.4401	0	14081822
DN100	PN10	PN10	56	ELA60	24V DC	FPM (FKM)	Stainless steel	1.4401	0	14081841
DN100	PN10	PN10	56	ELA60	230 V AC	FPM (FKM)	Stainless steel	1.4401	0	14081830
DN125	PN10	PN10	66	ELA150	230 V AC	EPDM	Stainless steel	1.4401	0	14081812
DN125	PN10	PN10	66	ELA150	24V DC	EPDM	Stainless steel	1.4401	0	14081823
DN125	PN10	PN10	66	ELA150	24V DC	FPM (FKM)	Stainless steel	1.4401	0	14081842
DN125	PN10	PN10	66	ELA150	230 V AC	FPM (FKM)	Stainless steel	1.4401	0	14081831
DN150	PN10	PN10	71	ELA150	230 V AC	EPDM	Stainless steel	1.4401	0	14081813
DN150	PN10	PN10	71	ELA150	24V DC	EPDM	Stainless steel	1.4401	0	14081824
DN150	PN10	PN10	71	ELA200	24V DC	FPM (FKM)	Stainless steel	1.4401	0	14081843
DN150	PN10	PN10	71	ELA200	230 V AC	FPM (FKM)	Stainless steel	1.4401	0	14081832
DN200	PN10	PN10	87	ELA300	230 V AC	EPDM	Stainless steel	1.4401	0	14081814
DN200	PN10	PN10	87	ELA300	24V DC	EPDM	Stainless steel	1.4401	0	14081825
DN200	PN10	PN10	87	ELA500	230 V AC	FPM (FKM)	Stainless steel	1.4401	0	14081833
DN250	PN10	PN10		ELA500	230 V AC	EPDM	Stainless steel	1.4401	0	14081815
DN250	PN10	PN10		ELA600	230 V AC	FPM (FKM)	Stainless steel	1.4401	0	14081834
DN300	PN10	PN10		ELA600	230 V AC	EPDM	Stainless steel	1.4401	0	14081816

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal inner diameter	Pressure rating	Pressure rating flange	Face to Face length mm	Type coding actuator	Supply voltage	Material liner	Spindle material	Quality class spindle	Minimum medium temperature (continuous) °C	Article
DN300	PN10	PN10		ELA1200	230 V AC	FPM (FKM)	Stainless steel	1.4401	0	14081835
DN350	PN10	PN10		ELA800	230 V AC	EPDM	Stainless steel	1.4401	0	14081817
DN350	PN10	PN10		ELA1200	230 V AC	FPM (FKM)	Stainless steel	1.4401	0	14081836

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.