



ASAHI Butterfly valve Series: 57 Type: 3743EE PP/PP Electric operated Wafer type

Characteristics

Series: 57
Type: 3743EE
Norm: EN (DIN)
Valve design: Centric
Housing material: PP
Connection: Wafer type
Face to Face norm: Manufacturer standard
Operation: Electric operated
Brand actuator: ECON
Housing lining: Not replaceable

Disk material: PP
Primary spindle seal material: FPM (FKM)
Actuator material: Aluminium
Maximum medium temperature (continuous): 80 °C

Application

- Recommended in: Chemical

Nominal inner diameter	Pressure rating	Pressure rating flange	Face to Face length mm	Type coding actuator	Supply voltage	Material liner	Spindle material	Quality class spindle	Minimum medium temperature (continuous) °C	Article
DN40	PN10	PN10	39	ELA60	24V DC	EPDM	Stainless steel	1.4401	-20	14081855
DN40	PN10	PN10	39	ELA60	230 V AC	EPDM	Stainless steel	1.4401	-20	14081844
DN40	PN10	PN10	39	ELA60	24V DC	FPM (FKM)	Stainless steel	1.4401	-20	14081874
DN40	PN10	PN10	39	ELA60	230 V AC	FPM (FKM)	Stainless steel	1.4401	-20	14081863
DN50	PN10	PN10	42	ELA60	230 V AC	EPDM	Stainless steel	1.4401	-20	14081845
DN50	PN10	PN10	42	ELA60	24V DC	EPDM	Stainless steel	1.4401	-20	14081856
DN50	PN10	PN10	42	ELA60	230 V AC	FPM (FKM)	Stainless steel	1.4401	-20	14081864
DN50	PN10	PN10	42	ELA60	24V DC	FPM (FKM)	Stainless steel	1.4401	-20	14081875
DN65	PN10	PN10	46	ELA60	230 V AC	EPDM	Stainless steel	1.4401	-20	14081846
DN65	PN10	PN10	46	ELA60	24V DC	EPDM	Stainless steel	1.4401	-20	14081857
DN65	PN10	PN10	46	ELA60	24V DC	FPM (FKM)	Stainless steel	1.4401	-20	14081876
DN65	PN10	PN10	46	ELA60	230 V AC	FPM (FKM)	Stainless steel	1.4401	-20	14081865
DN80	PN10	PN10	46	ELA60	230 V AC	EPDM	Stainless steel	1.4401	-20	14081847
DN80	PN10	PN10	46	ELA60	24V DC	EPDM	Stainless steel	1.4401	-20	14081858
DN80	PN10	PN10	46	ELA60	24V DC	FPM (FKM)	Stainless steel	1.4401	-20	14081877
DN80	PN10	PN10	46	ELA60	230 V AC	FPM (FKM)	Stainless steel	1.4401	-20	14081866
DN100	PN10	PN10	56	ELA60	24V DC	EPDM	Stainless steel	1.4401	-20	14081859
DN100	PN10	PN10	56	ELA60	230 V AC	EPDM	Stainless steel	1.4401	-20	14081848
DN100	PN10	PN10	56	ELA60	230 V AC	FPM (FKM)	Stainless steel	1.4401	-20	14081867
DN100	PN10	PN10	56	ELA60	24V DC	FPM (FKM)	Stainless steel	1.4401	-20	14081878
DN125	PN10	PN10	66	ELA150	24V DC	EPDM	Stainless steel	1.4401	-20	14081860
DN125	PN10	PN10	66	ELA150	230 V AC	EPDM	Stainless steel	1.4401	-20	14081849
DN125	PN10	PN10	66	ELA150	230 V AC	FPM (FKM)	Stainless steel	1.4401	-20	14081868
DN125	PN10	PN10	66	ELA150	24V DC	FPM (FKM)	Stainless steel	1.4401	-20	14081879
DN150	PN10	PN10	71	ELA150	24V DC	EPDM	Stainless steel	1.4401	-20	14081861
DN150	PN10	PN10	71	ELA150	230 V AC	EPDM	Stainless steel	1.4401	-20	14081850
DN150	PN10	PN10	71	ELA200	230 V AC	FPM (FKM)	Stainless steel	1.4401	-20	14081869
DN150	PN10	PN10	71	ELA200	24V DC	FPM (FKM)	Stainless steel	1.4401	-20	14081880
DN200	PN10	PN10	87	ELA300	24V DC	EPDM	Stainless steel	1.4401	-20	14081862
DN200	PN10	PN10	87	ELA300	230 V AC	EPDM	Stainless steel	1.4401	-20	14081851
DN200	PN10	PN10	87	ELA500	230 V AC	FPM (FKM)	Stainless steel	1.4401	-20	14081870
DN250	PN10	PN10	110	ELA500	230 V AC	EPDM	Stainless steel	1.4401	-20	14081852
DN250	PN10	PN10	110	ELA600	230 V AC	FPM (FKM)	Stainless steel	1.4401	-20	14081871
DN300	PN10	PN10	129	ELA600	230 V AC	EPDM	Stainless steel	1.4401	-20	14081853

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal inner diameter	Pressure rating	Pressure rating flange	Face to Face length mm	Type coding actuator	Supply voltage	Material liner	Spindle material	Quality class spindle	Minimum medium temperature (continuous) °C	Article
DN300	PN10	PN10	129	ELA1200	230 V AC	FPM (FKM)	Stainless steel	1.4401	-20	14081872
DN350	PN10	PN10	129	ELA800	230 V AC	EPDM	Stainless steel	1.4401	-20	14081854
DN350	PN10	PN10	129	ELA1200	230 V AC	FPM (FKM)	Stainless steel	1.4401	-20	14081873

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.