



OLEODINAMICA MARCHESINI T-shape double pressure-limiting valve with anti-cavitation valves VAUAC

This valve is used to block pressure to a certain setting in the 2 ports of an hydraulic motor: when it reaches pressure setting, the valve opens allowing pressure relief in T. The relief valve provides overload protection in a fast and accuratere and cavitation is avoid thanks to the check valve.

Material:

- Body: zinc-plated steel.
- Internal parts: hardened and ground steel.
- Seals: BUNA N.

Mounting:

- BSP ports.



Characteristics

Version: Inline mounting

Type of valve: Cross-over valve

Material: Steel

Max. operating pressure bar	Max. oilflow l/min	Adjustment range	Connections	Article
350	45	10 - 180 bar	3/8" BSP	14229038
350	45	80 - 300 bar	3/8" BSP	14229039
350	70	10 - 180 bar	1/2" BSP	14229040
350	70	80 - 300 bar	1/2" BSP	14229041
350	110	20 - 200 bar	3/4" BSP	14229042
350	110	50 - 400 bar	3/4" BSP	14229043

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.