



LEADER PTFE flange gasket CLIPPERLON 2115 EN 1514-1

Characteristics

Series: CLIPPERLON

Type: 2115

Norm: EN 1514-1 IBC

Material structure: PTFE, modified

Marking: Unprinted

Temperature range: -210 / 260 °C

Max. pressure: 55 bar

Suitable for medium: Air (compressed air), Pharma, Hydrocarbons, Cryogenic, Refrigerants, Chlorine, gaseous [7782-50-5], Low pressure steam, Acids, Weak Alkalis, Weak Acids, Alkalis, Fuels, Chlorine Water < 5% [7782-50-5], Food & Beverages, Solvents

Approval according to: FDA 21 CFR 177.1550, TA-Luft, EC1935 [10/2011]

Application

- Recommended in: Chemical, Food & Beverages, Pharma

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
DN15	PN10/40	51	22	2	13411305
DN20	PN10/40	61	27	2	13411306
DN25	PN10/40	71	34	2	13411307
DN32	PN10/40	82	43	2	13547446
DN40	PN10/40	92	49	2	13412082
DN50	PN10/40	107	61	2	13411308
DN65	PN10/40	127	77	2	13412095
DN80	PN10/40	142	89	2	13411309
DN100	PN10/16	162	115	2	13411310
DN125	PN10/16	192	141	2	13419397
DN150	PN10/16	218	169	2	13419398
DN200	PN10/16	273	220	2	13419399

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.