



## ASAHI Butterfly valve Series: 57 Type: 3743EE PP/PVDF Electric operated Wafer type

### Characteristics

**Series:** 57  
**Type:** 3743EE  
**Norm:** EN (DIN)  
**Valve design:** Centric  
**Housing material:** PP  
**Connection:** Wafer type  
**Face to Face norm:** Manufacturer standard  
**Operation:** Electric operated  
**Brand actuator:** ECON  
**Housing lining:** Not replaceable

**Disk material:** PVDF

**Primary spindle seal material:** FPM (FKM)

**Actuator material:** Aluminium

**Maximum medium temperature (continuous):** 120 °C

### Application

- Recommended in: Chemical

Nominal inner diameter	Pressure rating	Pressure rating flange	Face to Face length mm	Type coding actuator	Supply voltage	Material liner	Spindle material	Quality class spindle	Minimum medium temperature (continuous) °C	Article
DN40	PN10	PN10	39	ELA60	230 V AC	FPM (FKM)	Stainless steel	1.4401	-20	14081881
DN40	PN10	PN10	39	ELA60	24V DC	FPM (FKM)	Stainless steel	1.4401	-20	14081892
DN50	PN10	PN10	42	ELA60	24V DC	FPM (FKM)	Stainless steel	1.4401	-20	14081893
DN50	PN10	PN10	42	ELA60	230 V AC	FPM (FKM)	Stainless steel	1.4401	-20	14081882
DN65	PN10	PN10	46	ELA60	24V DC	FPM (FKM)	Stainless steel	1.4401	-20	14081894
DN65	PN10	PN10	46	ELA60	230 V AC	FPM (FKM)	Stainless steel	1.4401	-20	14081883
DN80	PN10	PN10	46	ELA60	230 V AC	FPM (FKM)	Stainless steel	1.4401	-20	14081884
DN80	PN10	PN10	46	ELA60	24V DC	FPM (FKM)	Stainless steel	1.4401	-20	14081895
DN100	PN10	PN10	56	ELA60	24V DC	FPM (FKM)	Stainless steel	1.4401	-20	14081896
DN100	PN10	PN10	56	ELA60	230 V AC	FPM (FKM)	Stainless steel	1.4401	-20	14081885
DN125	PN10	PN10	66	ELA150	230 V AC	FPM (FKM)	Stainless steel	1.4401	-20	14081886
DN125	PN10	PN10	66	ELA150	24V DC	FPM (FKM)	Stainless steel	1.4401	-20	14081897
DN150	PN10	PN10	71	ELA200	230 V AC	FPM (FKM)	Stainless steel	1.4401	-20	14081887
DN150	PN10	PN10	71	ELA200	24V DC	FPM (FKM)	Stainless steel	1.4401	-20	14081898
DN200	PN10	PN10	87	ELA500	230 V AC	FPM (FKM)	Stainless steel	1.4401	-20	14081888
DN250	PN10	PN10	110	ELA600	230 V AC	FPM (FKM)	Stainless steel	1.4401	-20	14081889
DN300	PN10	PN10	129	ELA1200	230 V AC	FPM (FKM)	Stainless steel	1.4401	-20	14081890
DN350	PN10	PN10	129	ELA1200	230 V AC	FPM (FKM)	Stainless steel	1.4401	-20	14081891

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.