



ASAHI Butterfly valve Series: 57 Type: 3743ES PP/PVDF Pneumatic operated Single acting, spring closing Wafer type

Characteristics

Series: 57
Type: 3743ES
Norm: EN (DIN)
Valve design: Centric
Housing material: PP
Connection: Wafer type
Face to Face norm: Manufacturer standard
Operation: Pneumatic operated
Operating principle: Single acting, spring closing

Brand actuator: ECON
Housing lining: Not replaceable
Disk material: PVDF
Primary spindle seal material: FKM-F
Actuator material: Aluminium

Application

- Recommended in: Chemical

Nominal inner diameter	Pressure rating	Pressure rating flange	Face to Face length mm	Type coding actuator	Material liner	Spindle material	Quality class spindle	Minimum medium temperature (continuous) °C	Maximum medium temperature (continuous) °C	Article
DN40	PN10	PN10	39	SR40	FKM-F	Stainless steel	1.4401	-20	120	13414323
DN50	PN10	PN10	42	SR40	FKM-F	Stainless steel	1.4401	-20	120	13414324
DN65	PN10	PN10	46	SR80	FKM-F	Stainless steel	1.4401	-20	120	13414325
DN80	PN10	PN10	46	SR130	FKM-F	Stainless steel	1.4401	-20	120	13414326
DN100	PN10	PN10	56	SR130	FKM-F	Stainless steel	1.4401	-20	120	13414327
DN125	PN10	PN10	66	SR200	FKM-F	Stainless steel	1.4401	-20	120	13414328
DN150	PN10	PN10	71	SR200	FKM-F	Stainless steel	1.4401	-20	120	13414329
DN200	PN10	PN10	87	SR850	FKM-F	Stainless steel	1.4401	-20	120	13414330

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.