



FLEXION Plastic tubing Polyurethane/Polyester 958

These tubes are made of polyurethane polyester shore 98 A and are used in 90% of the pneumatic applications up to 8 bar of pressure. Their high flexibility, combined with tight bending radius and anti-kink behavior is very well appreciated.

Characteristics

Hose material: Polyurethane/Polyester

Internal diameter	Wall thickness	Outer diameter	Roller length	Colour	Minimum bending radius	Hardness	Minimum burst pressure	Maximum operating pressure at 23 °C	Article
mm	mm	mm	m		mm		bar	bar	
2.5	0.75	4	25	Green	10	98	46	15	14402809
2.5	0.75	4	25	Natural	10	98	46	15	14402614
2.5	0.75	4	25	Red	10	98	46	15	14403101
2.5	0.75	4	25	Yellow	10	98	46	15	14402679
4	1	6	25	Green	20	98	40	13	14403116
4	1	6	25	Natural	20	98	40	13	14402827
4	1	6	25	Red	20	98	40	13	14403279
4	1	6	25	Yellow	20	98	40	13	14402979
7	1.5	10	25	Green	25	98	35	12	14402991
7	1.5	10	25	Natural	25	98	35	12	14402704
7	1.5	10	25	Red	25	98	35	12	14403215
7	1.5	10	25	Yellow	25	98	35	12	14402839
8	2	12	25	Green	35	98	40	13	14402997
8	2	12	25	Natural	35	98	40	13	14402710
8	2	12	25	Red	35	98	40	13	14403217
8	2	12	25	Yellow	35	98	40	13	14402848

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.