




WIKA Temperature sensor fig. 30080 Pt100 series TR36 stainless steel compact connection plug

Characteristics

Series: TR36
Type: 30080
Type of connection head: Compact with plug
Accuracy class: Class A IEC 60751
With display: No
With pocket tube: No
Sensor diameter: 6 mm
Process connection material: Stainless steel 316Ti
Material connection head: Stainless steel 304

Characteristics [2]

Sensor material: Stainless steel 316Ti
Electrical connection: Plug EN 175301-803 type A
Level of protection (IP value): IP65
Explosion-proof: No
Max. operating pressure: 140 bar
Ambient temperature: -40 / 85 °C



Size table:

G	b mm	c mm	d mm	L mm	SW mm
1/2"	48	75	6	50-100-150-200	27
1/4"	48	75	6	50-100-150-200	27

Measuring element	Measuring insert	Measuring range °C	Process connection	Size process connection	With neck	Insert length mm	Article
Pt100 3 wires	No	-30 / 150	External thread	1/2" BSPP(G)	No	50	14378764
Pt100 3 wires	No	-30 / 150	External thread	1/2" BSPP(G)	No	100	14378767
Pt100 3 wires	No	-30 / 150	External thread	1/2" BSPP(G)	No	150	14378766
Pt100 3 wires	No	-30 / 150	External thread	1/4" BSPP(G)	No	50	14316986
Pt100 3 wires	No	-30 / 150	External thread	1/4" BSPP(G)	No	100	14316987
Pt100 3 wires	No	-30 / 150	External thread	1/4" BSPP(G)	No	150	14316985

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.