



## FESTO 3-Way ball valve Series: VZBA Stainless steel Pneumatic operated Internal thread (BSPP) PN63

### Characteristics

**Series:** VZBA

**Construction type:** 3-way

**Housing construction:** 4-part

**Housing material:** Stainless steel

**Material quality:** 1.4408

**Connection:** Internal thread (BSPP)

**Actuator:** Pneumatic operated

**Operating principle:** Double acting

**Body seal:** PTFE

Nominal inner diameter	Pressure rating	Mounting flange	Mounting flange 2	Ball bore	Material ball	Seat material	Spindle material	Minimum medium temperature [continuous] °C	Maximum medium temperature [continuous] °C	Article
1/4" [8]	PN63	F03	F04	T-bore	Stainless steel	PTFE	Stainless steel	-10	200	14169466
1/4" [8]	PN63			L-bore	Stainless steel	PTFE				14169458
1/2" [15]	PN63	F03	F04	L-bore	Stainless steel	PTFE	Stainless steel	-10	200	13684762
3/4" [20]	PN63	F04	F05	L-bore	Stainless steel	PTFE	Stainless steel	-10	200	14169462
3/4" [20]	PN63			T-bore	Stainless steel	PTFE				14169472
1" [25]	PN63	F04	F05	L-bore	Stainless steel	PTFE	Stainless steel	-10	200	14169464

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.