



FESTO Ball valve Series: VZBA Stainless steel Pneumatic operated Double acting Internal thread (BSPP) PN63

Characteristics

- Series:** VZBA
- Construction type:** 2-way
- Housing construction:** 3-part
- Housing material:** Stainless steel
- Material quality:** 1.4408
- Connection:** Internal thread (BSPP)
- Actuator:** Pneumatic operated
- Operating principle:** Double acting
- Top flange standard:** ISO 5211

Nominal inner diameter	Pressure rating	Mounting flange	Mounting flange 2	Material ball	Seat material	Spindle material	Body seal	Minimum medium temperature [continuous] °C	Maximum medium temperature [continuous] °C	Article
1/4" [8]	PN63	F03	F04	Stainless steel	PTFE	Stainless steel	PTFE	-10	200	12482709
3/8" [10]	PN63	F03	F04	Stainless steel	PTFE	Stainless steel	PTFE	-10	200	13403998
1" [25]	PN63	F04	F05	Stainless steel	PTFE	Stainless steel	PTFE	-10	200	12688807
1.1/4" [32]	PN63	F04	F05	Stainless steel	PTFE	Stainless steel	PTFE	-10	200	14169476

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.