



FESTO Ball valve Series: VZBA Stainless steel Butt weld EN 12627 PN63

Characteristics

Series: VZBA

Construction type: 2-way

Housing construction: 3-part

Housing material: Stainless steel

Material quality: 1.4408

Connection: Butt weld

Standard welding connection: EN 12627

Top flange standard: ISO 5211

Maximum medium temperature (continuous): 200 °C

Nominal inner diameter	Pressure rating	Manual operation	Mounting flange	Mounting flange 2	Material ball	Seat material	Spindle material	Body seal	Minimum medium temperature (continuous) °C	Article
1/4" [8]	PN63	Bare stem	F03	F04	Stainless steel	PTFE	Stainless steel	PTFE	-10	14168351
3/8" [10]	PN63	Bare stem	F03	F04	Stainless steel	PTFE	Stainless steel	PTFE	-10	14168350
1/2" [15]	PN63	Bare stem	F03	F04	Stainless steel	PTFE	Stainless steel	PTFE	-10	14168353
3/4" [20]	PN63	Bare stem	F03	F04	Stainless steel	PTFE	Stainless steel	PTFE	-10	13415895
1" [25]	PN63	Bare stem	F04	F05	Stainless steel	PTFE	Stainless steel	PTFE	-10	14168360
1.1/4" [32]	PN63	Bare stem	F04	F05	Stainless steel	PTFE	Stainless steel	PTFE	-10	14168452
1.1/2" [40]	PN63	Bare stem	F05	F07	Stainless steel	PTFE	Stainless steel	PTFE	-10	12672246
2" [50]	PN63	Bare stem	F05	F07	Stainless steel	PTFE	Stainless steel	PTFE	-10	14168404
2.1/2" [65]	PN63	Bare stem	F07	F10	Stainless steel	PTFE	Stainless steel	PTFE	-10	14168453
3" [80]	PN63	Bare stem	F07	F10	Stainless steel	PTFE	Stainless steel	PTFE	-10	12672252
4" [100]	PN63	Bare stem	F10		Stainless steel	PTFE	Stainless steel	PTFE	-10	14168439

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.