



GF Butterfly valve Series: 567 PVC-U/PVC-U Double-eccSilicone-free Handle Wafer type

Characteristics

Series: 567

Norm: EN (DIN)

Valve design: Double-eccentric

Housing material: PVC-U

Connection: Wafer type

Face to Face norm: Manufacturer standard

Operation: Handle

Disk material: PVC-U

Primary spindle seal material: EPDM

Silicone-free: Yes

Nominal inner diameter	Pressure rating	Pressure rating flange	Face to Face length mm	Material liner	Spindle material	Quality class spindle	Minimum medium temperature [continuous] °C	Maximum medium temperature [continuous] °C	Article
DN50	PN10	PN10	45	EPDM	Stainless steel	1.4000	0	60	12682256
DN65	PN10	PN10	46	EPDM	Stainless steel	1.4000	0	60	12682258
DN80	PN10	PN10	49	EPDM	Stainless steel	1.4000	0	60	12682259
DN100	PN10	PN10	56	EPDM	Stainless steel	1.4000	0	60	12682261
DN125	PN10	PN10	64	EPDM	Stainless steel	1.4000	0	60	12682262
DN150	PN10	PN10	72	EPDM	Stainless steel	1.4000	0	60	12682263
DN200	PN10	PN10	73	EPDM	Stainless steel	1.4000	0	60	12682265

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.